

PRODUCT RELEASE

For more information, contact
John O'Reilly
O'Reilly/DePalma
815-469-9100
john.oreilly@oreilly-depalma.com

Compact, Dual-Flush SANICOMPACT® Saves Water, Turns Tight Spaces into New Powder Rooms

The versatile, one-piece SANICOMPACT toilet from SFA Saniflo Inc. offers a reliable green solution that saves both water and floor space in a residential powder room application. The product installs quickly and easily anywhere in the home, with no venting required. In addition to handling toilet waste, the SANICOMPACT can also pump water away from a nearby sink.

Operating with either 1.28 or 1 gallon of water per flush (gpf), the self-contained SANICOMPACT can use up to 21% less water than a standard 1.28 gpf toilet.

That translates into a potential household savings of nearly 16 gallons of water per day, according to data from the U.S. Environmental protection agency. (See: http://www.epa.gov/watersense/docs/ws_indoor508.pdf).

Integrated design: SANICOMPACT saves space through a sleek, contemporary design that combines a macerating pump and a tank-less toilet bowl into a single fixture.

With this integrated design, the SANICOMPACT measures only 14.5 inches wide and 21.5 inches deep. That makes it ideal for tight spaces where installation space



THE SANICOMPACT CAN USE UP TO 21% LESS WATER PER FLUSH THAN A CONVENTIONAL TOILET, WHILE ITS COMPACT, ONE-PIECE DESIGN SAVES VALUABLE BATHROOM

SANIFLO

1-800-571-8191 | www.saniflo.com

is limited, such as in attics, pool houses, bedroom areas, basements and garages. The SANICOMPACT is ideal for installations under a stairway or in a closet to create an additional — even temporary — powder room. Its comparatively low, 18.5-inch height also provides easier, more comfortable access than a standard toilet.

Easy to operate: Made of vitreous china, the SANICOMPACT works in much the same manner as Saniflo's other systems, except that the pump and macerating unit are housed inside the fixture. Also, unlike a conventional toilet, the SANICOMPACT needs no external, gravity-flow tank. That's because the flushing-macerating cycle is automatic with a push of an electric button at the top of the bowl.

In addition to disposing waste from the toilet, the macerator inside can also pump water away from a nearby sink. The system uses a one-inch discharge pipe to pump effluent 9 feet vertically, 120 feet horizontally, or a combination of both. (Note: A vertical run of three feet is equivalent to a horizontal run of 30 feet.)

How it works: What follows is a step-by-step description of the flushing-macerating cycle in a SANICOMPACT:

- Pressing the electronic button activates a timer and a solenoid valve, filling the toilet bowl and washing its sides with water.
- Operating with a pressure of seven pounds per square inch (7 psi), the pump motor starts, drawing effluent and paper through the bowl and to the macerator, using either 1.28 or 1 gallon of water per flushing cycle.
- The cutting blades of the macerator quickly reduce the effluent, pumping it away through the one-inch discharge line.
- The pump motor stops within 14 seconds of its activation and the bowl automatically refills with fresh water to be ready for the next flush.



The SANICOMPACT carries a CSA mark for electrical use in the U.S.A. as well as Canada. Saniflo warrants the SANICOMPACT, including all electrical components, for two years.

SANICOMPACT – KEY SPECIFICATIONS:

- Dimensions (inches): 18.5H x 14.5W x 21.5D
- Motor Type: Induction, tested over 50,000 cycles; 3,600 rpm
- Amperage: 7.2
- Power Supply: 115 volts – 60 Hz
- Horsepower: 0.3
- Head: 9 feet
- Discharge: Horizontally – 120 feet; vertically – 9 feet
- Flush Volume: 1.28 to 1 gallon per flush
- Discharge pipe diameter: 1 inch
- Maximum water temperature (at hand basin): 95° F/35° C

###

SFA SANIFLO INC. is the only manufacturer of its kind in North America, offering a complete line of macerating toilet systems and gray water pumping systems for residential and commercial applications. Saniflo markets through independent sales agents throughout North America, and the product line is currently available at distributor and dealer locations throughout the United States and Canada.

For more information, contact Saniflo at 1-800-571-8191. Or visit the Saniflo website at www.saniflo.com.

For editorial assistance, including photography, contact John O'Reilly c/o O'Reilly/DePalma: 815-469-9100 or john.oreilly@oreilly-depalma.com

To download a hi-res .tif file of images to accompany this article, use this link <http://bit.ly/8pdY71>