PRESS RELEASE

For more information, contact John O'Reilly O'Reilly-DePalma 815-469-9100 john.oreilly@oreilly-depalma.com

Compact, Dual-Flush Sanicompact® Saves Water, Turns Tight Spaces into New Powder Rooms

Using only 1.0 to 1.28 gallons of water per flush, this one-piece, macerating toilet offers above-floor plumbing solution for creating a new bath in small spaces with no below-floor drainage.

EDISON, N.J. (APRIL 10, 2015) — The versatile, one-piece SANICOMPACT toilet from SFA Saniflo Inc. offers a reliable green solution that saves both water and floor space in a residential powder room application. The product installs quickly and easily anywhere in the home, with no venting required. Equipped with a dual-flush push button, SANICOMPACT allows the user to control the gallons used per flush and conserve



water. In addition to handling toilet waste, the SANICOMPACT can also pump water away from a nearby sink.

Operating with either 1 or 1.28 gallons of water per flush (gpf), the self-contained SANICOMPACT can use up to 21 percent less water than a standard 1.28 gpf toilet. That translates into a potential household savings of nearly 16 gallons of water per day, according to data from the U.S. Environmental protection agency. (See: http://www.epa.gov/watersense/docs/ws_indoor508.pdf).

Integrated design: Sanicompact saves space through a sleek, contemporary design that combines a macerating pump and a tank-less toilet bowl into a single fixture.

-more on next page-



With this integrated design, the Sanicompact measures only 14.5 inches wide and 21.5 inches deep. That makes it ideal for tight areas where installation space is limited, such as in attics, pool houses, bedroom areas, basements and garages. The Sanicompact is ideal for installations under a stairway or in a closet to create an additional — even temporary — powder room. Its comparatively low, 18.5-inch height also provides easier, more comfortable access than a standard toilet.

Easy to operate: Made of vitreous china, the SANICOMPACT works in much the same manner as Saniflo's other systems, except that the pump and macerating unit are housed inside the fixture. Also, unlike a conventional toilet, the SANICOMPACT needs no external, gravity-flow tank. That's because the flushing-macerating cycle is automatic with a push of an electric button at the top of the bowl.

The system uses a one-inch discharge pipe to pump effluent 9 feet vertically, 120 feet horizontally, or a combination of both. (Note: A vertical run of three feet is equivalent to a horizontal run of 30 feet.)

How it works: What follows is a step-by-step description of the flushing-macerating cycle in a SANICOMPACT:

- Pressing the electronic button activates a timer and a solenoid valve, filling the toilet bowl and washing its sides with water.
- Operating with a pressure of seven pounds per square inch (7 psi), the pump motor starts, drawing effluent and paper through the bowl and to the macerator, using either 1.28 or 1 gallon of water per flushing cycle.
- The cutting blades of the macerator quickly reduce the effluent, pumping it away through the one-inch discharge line.
- The pump motor stops within 14 seconds of its activation and the bowl automatically refills with fresh water to be ready for the next flush.

The SANICOMPACT carries a CSA mark for electrical use in the U.S.A. as well as Canada. Saniflo warranties the SANICOMPACT, including all electrical components, for two years.

-more on next page-

COMPACT, DUAL-FLUSH SANICOMPACT® SAVES WATER, TURNS TIGHT SPACES INTO NEW POWDER ROOMS Page 3 of 3

SFA SANIFLO U.S.A. — whose parent company originated macerating plumbing technology — offers a complete line of up flush toilets and gray water pumping systems for residential and commercial applications. Saniflo developed its innovative, "above-floor plumbing" technology more than a half-century ago and has led its commercialization worldwide. Today, the company markets macerating technology through 22 subsidiaries in 50 countries and has sold more than six million units worldwide since 1958. Saniflo markets through independent sales agents throughout North America, and the product line is currently available at distributor and dealer locations throughout the United States and Canada.

- For more information, contact Saniflo at 1-800-571-8191. Or visit the Saniflo website at www.saniflo.com.
- For editorial assistance, including photography, contact John O'Reilly or Tony Bara c/o O'Reilly-DePalma: 815-469-9100 or john.oreilly@oreilly-depalma.com; tony.bara@oreilly-depalma.com.
- To download images (hi-res .tif files) to accompany this article, use this link: http://saniflo.oreilly-depalma.com/2015/sanicompact-saves-water.shtml.